M2M3 M2M3FD

bradbury security

Steel Door Sizes (Level 3)

- Single Doors: **Certified** - Max Width -1180mm X Max Height 2430mm
  (Pending Certification – 1430mmW X 2930mmH)
- Leaf & Half Doors: **Certified** - Max Width 2200mm X Max Height 2430mm
  (Pending Certification – 2600mmW X 2930mmH)
- Double Doors: **Certified** - Max Width 2200mm X Max Height 2430mm
  (Pending Certification – 2600mmW X 2930mmH)

Steel Door Frame (Level 3)

- Triple protection anti-pry frame profile
- Internal steel hinge chassis system for extra strength and rigidity, plus integral mounting plates
- Security door frame manufactured from 2mm thick Zintec steel
- 110mm frame depth
- Integral mounting plates
- Prepared for inside and outside fixing
- P Seals

Steel Door Leaf (Level 3)

- Manufactured from 1.5mm thick Zintec steel
- Folded 66mm thick leaf with composite Dufaylite honeycomb core
- Internal reinforcements and strengthened locking area
- 9 no. 17 mm solid steel dog bolts per leaf (18 on double doors)

Steel Door Hinges (Level 3)

- 6 no. BS.EN 1935.2002 Grade 13 stainless steel hinges per leaf, or option of 125mm lift-off hinges

Options (Level 3)

- Locking systems and actuators
- Access control options
- Glazing/vision panels - including DDA compliant vision panels
- Punched louvres
- Removable over panels, fixed side panels and fixed over panels available
- Powder coating or priming, including Extra Life 10 Year Paint warranty option

FIRE-RATED OPTIONS ALSO AVAILABLE – CERTIFIED UP TO 240 MINUTES

LPCB Bradbury Security M2M3 Assessed to LPS1175: Issue 7 Cert No. 312e Security Rating 3

Secured by Design SBD Official Police Security Initiative

constructionline

CHAS Contractors Health & Safety Assessment Scheme Accredited Contractor www.chas.gov.uk

bsia british security industry association

UVDB empowered by Achilles Registered